

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: BATTERY TERMINAL PROTECTOR

Product Code(s) : BTP6C

Recommended use of the chemical and restrictions on use

: Automotive - Coatings (aerosol).
Restrictions on use: Not available.

Chemical family : Mixture of: Mineral spirits; Viscosity control agent; Propellant; Dyes

Name, address, and telephone number of the supplier:

Radiator Specialty Co., of Canada

3-3055 Dundas St West, Suite 50
Mississauga, ON, Canada
L5L 3R8

Supplier's Telephone # : (905) 625-9117 (Mon. - Fri., 8 am - 4 pm)

24 Hr. Emergency Tel # : Not available.

Name, address, and telephone number of the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear, reddish liquid, contained in pressurized aerosol can. Hydrocarbon odour.

Most important hazards:

Extremely flammable aerosol. May be ignited by open flames and sparks. Contents under pressure. Container may explode if heated.

Aspiration hazard. Can enter the lungs and cause damage. Irritating to eyes and skin. Inhalation may cause central nervous system depression. Causes damage to organs through prolonged or repeated exposure. Occupational exposure to the substance or mixture may cause adverse effects. Refer also to TOXICOLOGICAL INFORMATION (Section 11).

Toxic to aquatic life with long lasting effects. Avoid release to the environment. See Section 12 for more environmental information.

This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)]. The below WHMIS 2015 classification and labeling information is being provided for informational purposes.

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).
Classification:

Flammable aerosol - Category 1

Gases under pressure - Compressed gas

Aspiration toxicity - Category 1

Skin corrosion/irritation - Category 2

Eye damage/irritation - Category 2A

Specific target organ toxicity, single exposure - Category 3(Narcotic effects)

Specific target organ toxicity, repeated exposure - Category 1

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

SAFETY DATA SHEET

Hazard statement(s)

Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.
 Causes damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe the mist or vapor.
 Wash exposed skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves and eye/face protection.

Get medical advice/attention if you feel unwell.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
 IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local regulation.

Other hazards*Other hazards which do not result in classification:*

Toxic fumes may be released during a fire. Mild respiratory irritant. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache). Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Mineral spirits			80.0 - 100.0
<i>This material is a mixture of the following chemicals:</i>			
stoddard solvent	Mineral spirits White spirit	8052-41-3	
Solvent naphtha (petroleum), medium aliphatic	White spirit stoddard solvent	64742-88-7	
Naphtha (petroleum), hydrotreated heavy	Odorless mineral spirits Hydrotreated heavy naphtha	64742-48-9	
Polyisobutylenes	Isobutylene polymer Poly(2-methylpropene)	9003-27-4	1.0 - 5.0
Carbon dioxide	Carbonic anhydride	124-38-9	1.0 - 5.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

Note: This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)].

SAFETY DATA SHEET

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing stops, provide artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.
- Skin contact* : IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Flush eyes with water for at least 15 minutes. If eye irritation persists: get medical advice/attention.

Most important symptoms and effects, both acute and delayed

- : May be fatal if swallowed and enters airways. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Causes skin irritation. Contact may cause redness, swelling and a painful sensation. Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis. May cause central nervous system effects. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Causes damage to organs through prolonged or repeated exposure. May result in irreversible neurological symptoms such as problems with memory, visuospatial skills (e.g. depth perception), fatigue, muscle control, peripheral nerves (e.g. tingling in the hands and feet), and seizures. Mild respiratory irritant. May cause coughing and breathing difficulties. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache). Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Provide general supportive measures and treat symptomatically. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Carbon dioxide (CO₂); Dry chemical; Alcohol resistant foam; Water fog.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Extremely flammable aerosol. May be ignited by open flames and sparks. This product is contained under pressure, and could explode when exposed to heat and flame. Vapours may be heavier than air and may collect in confined and low-lying areas. Material will float on water and can be re-ignited at the water's surface.

Hazardous combustion products

- : Carbon oxides; Reactive hydrocarbons; Aldehydes; Other unidentified organic compounds.

SAFETY DATA SHEET

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Shield personnel to protect from venting or rupturing containers. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Wear appropriate protective equipment. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

- : Prevent product from entering drains, sewers, waterways and soil. Avoid release to the environment.

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Keep in properly labelled containers. Notify the appropriate authorities as required. Refer to Section 13 for disposal of contaminated material.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective gloves and eye/face protection. Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Keep away from incompatibles. Always replace cap after use. Wash thoroughly after handling.

Conditions for safe storage

- : Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Keep away from incompatibles.

Incompatible materials

- : Strong oxidizing agents; Strong bases; Reducing agents

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>				
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
stoddard solvent	100 ppm	N/Av	500 ppm (2900 mg/m ³)	N/Av
Solvent naphtha (petroleum), medium aliphatic	N/Av	N/Av	500 ppm (2000 mg/m ³) (as petroleum distillates, naphtha)	N/Av

SAFETY DATA SHEET

Naphtha (petroleum), hydrotreated heavy	N/Av	N/Av	N/Av	N/Av
Polyisobutylenes	N/Av	N/Av	N/Av	N/Av
Carbon dioxide	5000 ppm	30 000 ppm	5000 ppm (9000 mg/m ³)	N/Av

Exposure controls**Ventilation and engineering measures**

- : Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Refer to CSA Z94.3 or other appropriate standards. Advice should be sought from respiratory protection specialists.

Skin protection

- : Wear protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Depending on conditions of use, an impervious apron should be worn. Wear sufficient clothing to prevent skin contact.

Eye / face protection

- : Wear eye/face protection. Wear as appropriate: Safety glasses with side shields; Tightly fitting safety goggles. A full face shield may also be necessary.

Other protective equipment

- : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear, reddish liquid, contained in pressurized aerosol can.

Odour : Hydrocarbon odour.

Odour threshold : N/Av

pH : N/Av

Melting/Freezing point : - 70°C (- 94°F) (estimation)

Initial boiling point and boiling range

: 157°C (314.6°F) (estimation)

Flash point : 42.2°C (108°F) (concentrate)

Flashpoint (Method) : N/Av

Evaporation rate (BuAe = 1) : N/Av

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

: 0.7% (estimation)

Upper flammable limit (% by vol.)

: 6.0% (estimation)

Oxidizing properties : No oxidizing properties.

Explosive properties : Aerosols are sensitive to mechanical impact. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time.

Vapour pressure : 0.29 hPa (estimated)

Vapour density : N/Av

Relative density / Specific gravity

: Relative density: 800 kg/m³ (estimated)
Specific Gravity: 0.8 (estimated)

Solubility in water : Insoluble.

Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : 109.44°C (229°F) (estimation)

Decomposition temperature : N/Av

SAFETY DATA SHEET

Viscosity : < 14 mm²/sec @ 40°C (104°F) (estimation)
Volatiles (% by weight) : 4.72% (estimated)
Volatile organic Compounds (VOC's)
: N/Av
Absolute pressure of container
: N/Av
Flame projection length : 73.7 cm (29")
Other physical/chemical comments
: Flashback Observed: NO
Chemical heat of combustion: 34.44 kJ/g (estimated)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions
: Hazardous polymerization does not occur.
Conditions to avoid : Direct sources of heat. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
Incompatible materials : Strong oxidizing agents; Strong bases; Reducing agents
Hazardous decomposition products
: Not available.
In the event of fire: Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption
: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: Mild respiratory irritant. May cause coughing and breathing difficulties. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness. In extremely high concentrations, product may act as an asphyxiant and cause increased breathing and pulse rates, fatigue and unconsciousness.

Sign and symptoms ingestion

: May be fatal if swallowed and enters airways. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache).

Sign and symptoms skin

: May cause moderate to severe skin irritation. Contact may cause redness, swelling and a painful sensation.

Sign and symptoms eyes

: Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects

: Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

Mutagenicity

: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

SAFETY DATA SHEET

Carcinogenicity : Not classifiable as a human carcinogen. No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: This product is not expected to cause reproductive or developmental effects.

Sensitization to material : No data available to indicate product or components may be respiratory sensitizers. No data available to indicate product or components may be skin sensitizers.

Specific target organ effects : This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:
Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or dizziness.
Specific target organ toxicity, repeated exposure - Category 1. Causes damage to organs through prolonged or repeated exposure. Contains: stoddard solvent. May result in irreversible neurological symptoms such as problems with memory, visuospatial skills (e.g. depth perception), fatigue, muscle control, peripheral nerves (e.g. tingling in the hands and feet), and seizures.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

: None known or reported by the manufacturer.

Toxicological data

: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC₅₀ (4hr)</u> <u>inh, rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Mineral spirits <i>This material is a mixture of the following chemicals:</i>			
stoddard solvent	> 5.5 mg/L (vapour)	> 5000 mg/kg	> 3000 mg/kg
Solvent naphtha (petroleum), medium aliphatic	> 5.5 mg/L (vapour)	> 5000 mg/kg (No mortality)	> 2000 mg/kg (No mortality)
Naphtha (petroleum), hydrotreated heavy	> 5.04 mg/L (vapour)	> 7000 mg/kg	> 2000 mg/kg (No mortality)
Polyisobutylenes	N/Av	> 2000 mg/kg (No mortality)	N/Av
Carbon dioxide	200 000 ppm/2H (141 421 ppm/4H)	N/Ap (gas)	N/Ap (gas)

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : Toxic to aquatic life with long lasting effects. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. The product contains the following substances which are hazardous for the environment: Mineral spirits.

See the following tables for individual ingredient ecotoxicity data.

SAFETY DATA SHEET

Ecotoxicity data:

<u>Ingredients</u>	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
stoddard solvent	8052-41-3	2.1 - 4.2 mg/L (Bluegill sunfish)	N/Av	None.
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	2 - 5 mg/L (Rainbow trout)	0.098 mg/L/28-day (QSAR) (NOEL)	None.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	8.2 mg/L (Fathead minnow)	N/Av	None.
Polyisobutylenes	9003-27-4	> 5600 mg/L (Rainbow trout)	N/Av	None.
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
stoddard solvent	8052-41-3	0.42 - 2.3 mg/L (Daphnia magna)	0.1 - 0.37 mg/L	None.
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	1.4 mg/L (Daphnia magna)	0.48 mg/L (QSAR) (NOEL)	None.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	32 mg/L (Daphnia magna)	6.3 mg/L	None.
Polyisobutylenes	9003-27-4	N/Av	N/Av	None.
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
stoddard solvent	8052-41-3	0.58 - 1.2 mg/L/72hr (Green algae)	0.16 mg/L/72hr	None.
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	1 - 3 mg/L/72hr (Green algae)	1 mg/L/72hr (Green algae) (NOEL)	None.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	45 mg/L/96hr (Green algae)	18 mg/L/96hr	None.
Polyisobutylenes	9003-27-4	N/Av	N/Av	None.
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap

Persistence and degradability

- : The product itself has not been tested.
The following ingredients are considered to be readily biodegradable: Mineral spirits.

Bioaccumulation potential

- : The product itself has not been tested. See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
stoddard solvent (CAS 8052-41-3)	3.16 - 7.06	N/Av
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	3.7 - 6.7	142 - 11,430 (Fish) (calculated)
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	2.1 - 6 (calculated)	10 - 2500 (calculated)
Polyisobutylenes (CAS 9003-27-4)	5	1.77

SAFETY DATA SHEET

Mobility in soil : The product itself has not been tested.

Other Adverse Environmental effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.


SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8. This material and its container must be disposed of in a safe way.

Empty containers retain residue and can be dangerous. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal : Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	None	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Under the TDG, refer to Section 1.17 for additional exemption requirements, if shipping under this exemption.				

Special precautions for user : Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:
 stoddard solvent (Part 5: Other groups and mixtures)
 Naphtha (petroleum), hydrotreated heavy (Part 5: Other groups and mixtures)
 Solvent naphtha (petroleum), medium aliphatic (Part 5: Other groups and mixtures)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
stoddard solvent	8052-41-3	232-489-3	Present	Present	(9)-1702; (9)-1702	KE-32199	Present	HSR001498

SAFETY DATA SHEET

Solvent naphtha (petroleum), medium aliphatic	64742-88-7	265-191-7	Present	Present	(9)-1700	KE-31664	Present	May be used as a single component chemical under an appropriate group standard.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	265-150-3	Present	Present	(9)-1690	KE-25622	Present	May be used as a single component chemical under an appropriate group standard.
Polyisobutylenes	9003-27-4	Polymer	Present	Present	(5)-774; (6)-774	KE-28918	Present	May be used as a single component chemical under an appropriate group standard.
Carbon dioxide	124-38-9	204-696-9	Present	Present	(1)-310; (1)-169	KE-04683	Present	HSR001018

SECTION 16. OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- AICS: Australian Inventory of Chemical Substances
- CAS: Chemical Abstract Services
- CSA: Canadian Standards Association
- EC50: Effective Concentration 50%
- EINECS: European Inventory of Existing Commercial chemical Substances
- ENCS: Existing and New Chemical Substances
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- IBC: Intermediate Bulk Container
- IECSC: Inventory of Existing Chemical Substances
- IMDG: International Maritime Dangerous Goods
- IOC: Inventory of Chemicals
- KECI: Korean Existing Chemicals Inventory
- KECL: Korean Existing Chemicals List
- LC: Lethal Concentration
- LD: Lethal Dose
- N/Av: Not Applicable
- N/Av: Not Available
- NIOSH: National Institute of Occupational Safety and Health
- NOEC: No observable effect concentration
- NTP: National Toxicology Program
- OECD: Organisation for Economic Co-operation and Development
- OSHA: Occupational Safety and Health Administration
- PEL: Permissible exposure limit
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- RTECS: Registry of Toxic Effects of Chemical Substances
- SCBA: Self-Contained Breathing Apparatus
- SDS: Safety Data Sheet
- STEL: Short Term Exposure Limit
- TDG: Canadian Transportation of Dangerous Goods Act & Regulations
- TLV: Threshold Limit Values
- TWA: Time Weighted Average
- WHMIS: Workplace Hazardous Materials Identification System

SAFETY DATA SHEET

- References** :
1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2018.
 2. International Agency for Research on Cancer Monographs, searched 2019.
 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2019 (Chempendium, HSDB and RTECs).
 4. Material Safety Data Sheets from manufacturer.
 5. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2019.

Preparation Date (mm/dd/yyyy) : 03/22/2019

Other special considerations for handling : Provide adequate information, instruction and training for operators.

<p><u>Prepared for:</u> Radiator Specialty Co. of Canada 3-3055 Dundas St West, Suite 50 Mississauga, ON, Canada, L5L 3R8 Telephone: 905-625-9117 (Mon. - Fri., 8 AM - 4 PM) Please direct all enquiries to Radiator Specialty.</p>	
<p><u>Prepared by:</u> ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

END OF DOCUMENT