BBI

SAFETY DATA SHEET

1. Identification

Product identifier Solder Seal/Gunk Cooling System Stop Leak

Other means of identification

SDS number C501

Part No. C501, C501V
Tariff code 7603.10.0000

Recommended use Radiator Sealer
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Blumenthal Brands Integrated, LLC

Address 600 Radiator Road

Indian Trail, NC 28079

Telephone Customer Service/ (704) 821-7643

Technical

Website www.solvewithB.com E-mail sds@solvewithB.com

Emergency phone number INFOTRAC (Domestic) (800) 535-5053

INFOTRAC (International) (352) 323-3500

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be

allowed out of the workplace. Wear protective gloves.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Category 1

Wash contaminated clothing before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: Solder Seal/Gunk Cooling System Stop Leak
C501, C501V Version #: 03 Revision date: 03-17-2020 Issue date: 05-28-2015

Supplemental information

98.71% of the mixture consists of component(s) of unknown acute oral toxicity. 98.71% of the mixture consists of component(s) of unknown acute dermal toxicity. 94.83% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 94.83% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminium (powder)		7429-90-5	1 - < 3
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	1 - < 3
N-(3-Chloroallyl)Hexaminium Chloride		4080-31-3	< 0.2
Other components below reportable le	vels		90 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important May cause an allergic skin reaction. Dermatitis. Rash.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods General fire hazards Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Aluminium (powder) (CAS 7429-90-5)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
US. OSHA Table Z-3 (29 CFR 1910.	-		_
Components	Туре	Value	Form
Aluminium (powder) (CAS 7429-90-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Aluminium (powder) (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
Aluminium (powder) (CAS 7429-90-5)	TWA	5 mg/m3	Welding fume or pyrophoric powder.
		5 mg/m3	Respirable.
		10 mg/m3	Total
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
- · · · = 0- 0,	STEL	10 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.

Dust mask.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance dedusted powder

Physical state Solid.
Form Powder.
Color bright
Odor bland

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 19.25024 lbs/gal estimated

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 2.3068 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. Conditions to avoid

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation May cause an allergic skin reaction. Skin contact

Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Test Results Components **Species**

Aluminium (powder) (CAS 7429-90-5)

Acute Oral

Rat LD50 > 2000 mg/kg

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)

Acute Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 3.9 mg/l, 4 Hours

Oral

LD50 Rat > 2000 mg/kg

N-(3-Chloroallyl)Hexaminium Chloride (CAS 4080-31-3)

Acute

Dermal

LD50 Rabbit 565 mg/kg

Oral

LD50 Rat 500 mg/kg

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

C501, C501V Version #: 03 Revision date: 03-17-2020 Issue date: 05-28-2015

^{*} Estimates for product may be based on additional component data not shown.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Aluminium (powder) (CAS 7429-90-5)

Aquatic

Fish LC50

Rainbow trout, donaldson trout (Oncorhynchus mykiss)

0.16 mg/l, 96 hours

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

N-(3-Chloroallyl)Hexaminium Chloride -0.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

^{*} Estimates for product may be based on additional component data not shown.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Aluminium (powder)	7429-90-5	1 - < 3	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

WARNING: This product contains a chemical known to the State of California to cause cancer. **US state regulations**

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Diethanolamine (CAS 111-42-2) Listed: June 22, 2012

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Aluminium (powder) (CAS 7429-90-5)

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)

International Inventories

Country(s) or region	Inventory name On in	ventory (yes/no)*			
Australia	Australian Inventory of Chemical Substances (AICS)	No			
Canada	Domestic Substances List (DSL)	Yes			
Canada	Non-Domestic Substances List (NDSL)	No			
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes			
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes			
Europe	European List of Notified Chemical Substances (ELINCS)	No			
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No			
Korea	Existing Chemicals List (ECL)	No			
New Zealand	New Zealand Inventory	Yes			
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No			
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes			
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes			
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)					

16. Other information, including date of preparation or last revision

Issue date 05-28-2015 03-17-2020 **Revision date**

Version # 03

Material name: Solder Seal/Gunk Cooling System Stop Leak

SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

HMIS® ratings Health: 2

Flammability: 0 Physical hazard: 0

NFPA ratings

Health: 2 Flammability: 0 Instability: 0

NFPA ratings



Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Product and Company Identification

SDS US