

SAFETY DATA SHEET

1. Identification

Product identifier	Engine Brite Heavy Duty Engine Degreaser	r
Other means of identification		
SDS number	EB1	
Part No.	EB1, EB1/6	
Tariff code	3814.00.5090	
Recommended use	Engine Degreaser	
Recommended restrictions	None known.	
Manufacturer/Importer/Suppl	ier/Distributor information	
Manufacturer		
Company name		
Address	Blaster LLC	
	8500 Sweet Valley Drive Valley	
Telephone	View, Ohio 44125 - USA T (216)901	
Website	F (216)901-5801	
Website	www.blastercorp.com	
Emergency phone number	·	
	Chemtrec (800) 424-9300	
2. Hazard(s) identificati	on	
Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Harmful if swallowed. May be fatal if swallowed and enters airways Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.	
Precautionary statement		
Prevention	and understood. Keep away from heat/sparks, spray on an open flame or other ignition sourc even after use. Do not breathe mist or vapor.	handle until all safety precautions have been read /open flames/hot surfaces No smoking. Do not ce. Pressurized container: Do not pierce or burn, Wash thoroughly after handling. Do not eat, drink or loors or in a well-ventilated area. Wear protective protection

gloves/protective clothing/eye protection/face protection.

Response	If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients

Chemical name	Common name and synonyms	CAS number	%
Petroleum Distillate Aliphatic		68476-34-6	60 - < 70
Kerosene		8008-20-6	20 - < 30
C9-15 Heavy Aromatic Hydrocarbons		64742-94-5	3 - < 5
Alkanes C10-20, Branched And Linear		928771-01-1	1 - < 3
Carbon Dioxide		124-38-9	1 - < 3
Poly(oxyethylene) Sorbitol Hexaoleate		57171-56-9	1 - < 3
Tert-butylbenzene		98-06-6	1 - < 3
Naphthalene		91-20-3	< 1
Other components below reportable levels			3 - < 5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Dry powder. Carbon dioxide (CO2).
I novitable ovtinguiabing	Do not use water jet as an extinguisher, as this will arread the fire

Suitable extinguishing media	Alconol resistant loant. Dry powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
6. Accidental release measures	

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Avoid discharge into drains, water courses or onto the ground.
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Level 3 Aerosol.
Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
C9-15 Heavy Aromatic Hydrocarbons (CAS 64742-94-5)	PEL	400 mg/m3	
		100 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Naphthalene (CAS 91-20-3)	PEL	50 mg/m3	

Components	Туре		Value	
			10 ppm	
US. ACGIH Threshold Limit	Values			
Components	Туре		Value	Form
C9-15 Heavy Aromatic Hydrocarbons (CAS 64742-94-5)	TWA		200 mg/m3	Non-aerosol.
Carbon Dioxide (CAS 124-38-9)	STEL		30000 ppm	
,	TWA		5000 ppm	
Kerosene (CAS 8008-20-6)	TWA		200 mg/m3	Non-aerosol.
Naphthalene (CAS 91-20-3)	TWA		10 ppm	
Petroleum Distillate Aliphatic (CAS 68476-34-6)	TWA		100 mg/m3	Inhalable fraction and vapor.
US. NIOSH: Pocket Guide to Components	Chemical Hazards Type		Value	
Carbon Dioxide (CAS	STEL		54000 mg/m3	
124-38-9)	STEL		54000 mg/m3	
			30000 ppm	
	TWA		9000 mg/m3	
			5000 ppm	
Kerosene (CAS 8008-20-6)	TWA		100 mg/m3	
Naphthalene (CAS 91-20-3)	STEL		75 mg/m3	
			15 ppm	
	TWA		50 mg/m3	
			10 ppm	
logical limit values	No biological exposure limits r	noted for the ingredie	ent(s).	
oosure guidelines		0		
US - California OELs: Skin d	esignation			
Naphthalene (CAS 91-20-	3)	Can be absorbed t	hrough the skin.	
US ACGIH Threshold Limit V	alues: Skin designation			
Kerosene (CAS 8008-20- Naphthalene (CAS 91-20-	3)	Can be absorbed t Can be absorbed t	hrough the skin. hrough the skin.	
Petroleum Distillate Alipha		Can be absorbed t	•	a used Mantilation rates
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilat or other engineering controls to maintain airborne levels below recommended exposure limits exposure limits have not been established, maintain airborne levels to an acceptable level. Pr eyewash station and safety shower.		es, local exhaust ventilation nmended exposure limits. I	
vidual protection measures,	such as personal protective e			
Eye/face protection	Chemical respirator with organ	nic vapor cartridge a	nd full facepiece.	
Skin protection				
Hand protection	Wear appropriate chemical res	sistant gloves.		
Other	Wear appropriate chemical res	sistant clothing. Use	of an impervious a	pron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.			
Thermal hazards	Wear appropriate thermal prot	ective clothing, when	n necessary.	
neral hygiene siderations	Observe any medical surveilla and drink. Always observe goo material and before eating, dri equipment to remove contami	od personal hygiene nking, and/or smokir	measures, such as	s washing after handling th

9. Physical and chemical properties

9. Physical and chemical	•
Appearance	Clear.
Physical state	Liquid.
Form	Aerosol.
Color	Red
Odor	Diesel Fuel odor
Odor threshold	Not available.
pН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	330 °F (165.56 °C) estimated
Flash point	136.0 °F (57.8 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	
Flammability limit - lower (%)	0.7 % estimated
Flammability limit - upper (%)	5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	2.66645 hPa estimated
Vapor density	Not available.
Relative density	0.834 g/cm3
Solubility(ies)	
Solubility (water)	0.1
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	None known.
Density	7.01 lbs/gal
Explosive properties	Not explosive.
Flammability (flash back)	No
Flammability class	Combustible II estimated
Heat of combustion (NFPA 30B)	39.8 kJ/g
Oxidizing properties	Not oxidizing.
Percent volatile	0.98 % estimated
Specific gravity	0.84
VOC	14.69 % estimated
10. Stability and reactivity	,

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
C9-15 Heavy Aromatic Hydrocart	oons (CAS 64742-94-5)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	< 5.8 mg/l, 4 Hours
Oral		
LD50	Rat	< 5000 mg/kg
		> 25 ml/kg
(erosene (CAS 8008-20-6)		
<u>Acute</u>		
Dermal	Dabbit	
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
Vapor LC50	Rat	> 0.1 mg/l, 8 Hours
Oral	Nat	
LD50	Rat	> 5000 mg/kg
Vaphthalene (CAS 91-20-3)		
Acute		
Dermal		
LD50	Rabbit	> 2 g/kg
Oral		
LD50	Rat	490 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye rritation	Causes serious eye irritation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall	Evaluation of Carcinogenicity	
Naphthalene (CAS 91-2		2B Possibly carcinogenic to humans.

Specific target organ toxicity - single exposureMay cause drowsiness and dizziness.Specific target organ toxicity - repeated exposureMay cause damage to organs through prolonged or repeated exposure.Aspiration hazardMay be fatal if swallowed and enters airways.	Petroleum Distillate Alipha	hatic (CAS 68476-34-6) 3 Not classifiable as to carcinogenicity to humans.	
US. National Toxicology Program (NTP) Report on Carcinogens Naphthalene (CAS 91-20-3)Reasonably Anticipated to be a Human Carcinogen.Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.Specific target organ toxicity - single exposureMay cause drowsiness and dizziness.Specific target organ toxicity - repeated exposureMay cause damage to organs through prolonged or repeated exposure.Aspiration hazardMay be fatal if swallowed and enters airways.Chronic effectsMay cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may	OSHA Specifically Regulate	d Substances (29 CFR 191	0.1001-1052)
Naphthalene (CAS 91-20-3)Reasonably Anticipated to be a Human Carcinogen.Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.Specific target organ toxicity - single exposureMay cause drowsiness and dizziness.Specific target organ toxicity - repeated exposureMay cause damage to organs through prolonged or repeated exposure.Aspiration hazardMay be fatal if swallowed and enters airways.Chronic effectsMay cause damage to organs through prolonged or repeated exposure.	Not regulated.		
Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.Specific target organ toxicity - single exposureMay cause drowsiness and dizziness.Specific target organ toxicity - repeated exposureMay cause damage to organs through prolonged or repeated exposure.Aspiration hazardMay be fatal if swallowed and enters airways.Chronic effectsMay cause damage to organs through prolonged or repeated exposure.	US. National Toxicology Pro	gram (NTP) Report on Car	cinogens
Specific target organ toxicity - single exposureMay cause drowsiness and dizziness.Specific target organ toxicity - repeated exposureMay cause damage to organs through prolonged or repeated exposure.Aspiration hazardMay be fatal if swallowed and enters airways.Chronic effectsMay cause damage to organs through prolonged or repeated exposure.	Naphthalene (CAS 91-20	-3)	Reasonably Anticipated to be a Human Carcinogen.
single exposureSpecific target organ toxicity - repeated exposureMay cause damage to organs through prolonged or repeated exposure.Aspiration hazardMay be fatal if swallowed and enters airways.Chronic effectsMay cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may	Reproductive toxicity	This product is not expected	ed to cause reproductive or developmental effects.
repeated exposureAspiration hazardMay be fatal if swallowed and enters airways.Chronic effectsMay cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may	Specific target organ toxicity - single exposure	May cause drowsiness and	d dizziness.
Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may	Specific target organ toxicity - repeated exposure	May cause damage to orga	ans through prolonged or repeated exposure.
	Aspiration hazard	May be fatal if swallowed a	and enters airways.
	Chronic effects		

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. Components **Species Test Results** C9-15 Heavy Aromatic Hydrocarbons (CAS 64742-94-5) Aquatic Crustacea **EC50** Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours Fish LC50 Rainbow trout, donaldson trout 8.8 mg/l, 96 hours (Oncorhynchus mykiss) 8.8 mg/l, 96 hours Naphthalene (CAS 91-20-3) Aquatic Crustacea **EC50** Water flea (Daphnia magna) 1.09 - 3.4 mg/l, 48 hours Fish LC50 Pink salmon (Oncorhynchus gorbuscha) 1.11 - 1.68 mg/l, 96 hours No data is available on the degradability of any ingredients in the mixture. Persistence and degradability **Bioaccumulative potential** Partition coefficient n-octanol / water (log Kow) Naphthalene 3.3 Tert-butylbenzene 4.11 Mobility in soil No data available. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/internationa regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

UN number


DOT

UN1950

potential.

Material name: Engine Brite Heavy Duty Engine Degreaser EB1, EB1/6 Version #: 12 Revision date: 02-20-2023 Issue date: 05-20-2015

UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity), Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	
Marine pollutant	No
· ·	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name Transport hazard class(es)	Aerosols, flammable, Limited Quantity
	2.1
Class Subsidiary risk	2.1
Packing group	- Not available.
Environmental hazards	No
ERG Code	10L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	· · · · · · · · · · · · · · · · · · ·
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	
Marine pollutant	No
EmS Special procedutions for use	F-D, S-U · Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	Not ostabilonou.
the IBC Code	
DOT; IMDG	
, -	





15. Regulatory information US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4)

Naphthalene (CAS 91-20-3)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard categoriesFlammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Carcinogenicity Specific target organ toxicity (single or repeated exposure) Aspiration hazard	
--	--

Listed.

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Naphthalene	91-20-3	< 1	_

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Naphthalene (CAS 91-20-3)

```
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
```

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Naphthalene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8)	Listed: April 6, 2010
Naphthalene (CAS 91-20-3)	Listed: April 19, 2002

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Kerosene (CAS 8008-20-6) Naphthalene (CAS 91-20-3) Petroleum Distillate Aliphatic (CAS 68476-34-6) Tert-butylbenzene (CAS 98-06-6)

Volatile organic compounds (VOC) regulations

EPA

Consumer products	Compliant
(40 CFR 59, Subpt. C)	

International Inventories

Country(s) or region	Inventory name Or	n inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Vaa" indicates that all some	nexts of this product comply with the inventory requirements administered by the governing	

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

-	•
Issue date	05-20-2015
Revision date	02-20-2023
Version #	12
HMIS® ratings	Health: 3* Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 2 Instability: 0
NFPA ratings	2 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Hazard(s) identification: Hazard statement Hazard(s) identification: Prevention Hazard(s) identification: Response Hazard(s) identification: GHS Symbols Hazard(s) identification: Supplemental information Accidental release measures: Methods and materials for containment and cleaning up Accidental release measures: Environmental precautions Physical & Chemical Properties: Multiple Properties Stability and reactivity: Possibility of hazardous reactions Ecological information: Ecotoxicity Transport Information: Material Transportation Information Transport information: General information GHS: Classification