

EBGELC Page 1 of 11

ENGINE BRITE GEL

SDS Preparation Date (mm/dd/yyyy): 03/31/2023

SECTION 1. IDENTIFICATION

Product identifier used on the label

: ENGINE BRITE GEL

Product Code(s) : EBGELC

Recommended use of the chemical and restrictions on use

: Engine degreaser / Cleaner. Restrictions on use: Not available.

Chemical family : Mixture of: Lubricating oil; Petroleum solvent; Lubricity improver; Surfactant; Propellant;

Glycol ether solvent; Terpene solvent

Manufacturer/Importer/Supplier/Distributor Information:

Company name Blaster LLC

Address 8500 Sweet Valley Drive

Valley View, Ohio 44125 - USA

Telephone (216)901-5800 (US)

(800)858-6605 (Canada) www.blastercorp.com

Emergency phone number : Chemtrec (800) 424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Grey liquid slurry, contained in pressurized aerosol can. Petroleum odour.

Most important hazards:

Website

Flammable aerosol. May be ignited by open flames and sparks. Contents under pressure. Container may explode if heated. Aspiration hazard. Can enter the lungs and cause damage. Irritating to eyes and skin. May cause an allergic skin reaction. Inhalation may cause central nervous system depression. Possible cancer hazard - contains material which may cause cancer. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS.

Toxic to aquatic life with long lasting effects. Avoid release to the environment. See Section 12 for more environmental information.

This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)]. The below WHMIS 2015 classification and labeling information is being provided for informational purposes.

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Flammable aerosol - Category 2

Gases under pressure

Aspiration toxicity - Category 1

Skin corrosion/irritation - Category 2

Eye damage/irritation - Category 2A

Skin sensitization - Category 1

Carcinogenicity - Category 1

Specific target organ toxicity, single exposure - Category 3 (Narcotic effects)

Label elements

Hazard pictogram(s)



Signal Word DANGER!

Hazard statement(s)

Flammable aerosol.

Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause cancer.

Precautionary statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid breathing mist or vapours.

Wash exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/clothing and eye/face protection.

IF exposed or concerned: Get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

Toxic fumes may be released during a fire. Mild respiratory irritant. Prolonged or repeated contact may cause drying, cracking and defatting of the skin. May cause gastrointestinal irritation. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS#	Concentration (% by weight)
Distillates (petroleum), hydrotreated light	Hydrotreated kerosene Isoparaffinic petroleum distillate	64742-47-8	65.0 - 85.0
Solvent naphtha (petroleum), heavy aromatic	Heavy Aromatic Naphtha	64742-94-5	5.0 - 10.0
Polyoxyethylene Sorbitol Hexaoleate	Sorbitol hexaoleate	57171-56-9	3.0 - 7.0
Carbon dioxide	Carbonic anhydride	124-38-9	1.0 - 5.0
d-Limonene	d-p-Mentha-1,8-diene 4-Isopropenyl-1-methylcyclohexen e	5989-27-5	1.0 - 5.0
Crystalline silica, quartz	Quartz silica Crystallized silicon dioxide	14808-60-7	0.1 - 1.0

Note: The exact concentrations of the above listed chemicals are being withheld as a trade secret.

EBGELC Page 3 of 11

SAFETY DATA SHEET

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion

: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

Inhalation

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing stops, provide artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

: IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Flush eyes with water for at least 15 minutes. If eye irritation persists: get medical advice/attention.

Most important symptoms and effects, both acute and delayed

 May be fatal if swallowed and enters airways. Aspiration hazard Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

Causes skin irritation. Contact may cause redness, swelling and a painful sensation. May cause severe skin sensitization with allergic contact dermatitis symptoms such as swelling, rash and eczema.

Causes serious eye irritation. Contact may cause redness, swelling and a painful sensation. May cause cancer. Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

Indication of any immediate medical attention and special treatment needed

: Immediate medical attention is required. Product may present an aspiration hazard, if ingested in large amounts, causing life-threatening lung injury.

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Carbon dioxide (CO2); Dry chemical; Alcohol resistant foam

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

Flammable aerosol. May be ignited by open flame. This product is contained under pressure, and could explode when exposed to heat and flame. Material will float on water and can be re-ignited at the water's surface. Toxic fumes, gases or vapours may evolve on burning.

Hazardous combustion products

: Carbon oxides; Reactive hydrocarbons; Aldehydes; Aromatic hydrocarbons; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

: Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Shield personnel to protect from venting or rupturing containers. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Wear appropriate protective equipment. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Prevent product from entering drains, sewers, waterways and soil. Avoid release to the environment.

Methods and material for containment and cleaning up

: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.
Refer to Section 13 for disposal of contaminated material.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Persons with recurrent skin eczema or sensitization problems should be excluded from working with this product. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted.

Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective gloves/clothing and eye/face protection. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Keep away from incompatibles. Always replace cap after use. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Conditions for safe storage

Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Keep away from incompatibles.

Incompatible materials

: Strong oxidizing agents; Strong acids; Strong alkalis; Halogenated compounds

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:						
Chemical Name	ACGIH T	<u> LV</u>	OSHA P	OSHA PEL		
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	STEL		
Distillates (petroleum), hydrotreated light	200 mg/m³ (as total hydrocarbon vapour)	N/Av	N/Av	N/Av		
Solvent naphtha (petroleum), heavy aromatic	N/Av	N/Av	500 ppm (2000 mg/m³) (as petroleum distillates, naphtha)	N/Av		
Polyoxyethylene Sorbitol Hexaoleate	N/Av	N/Av	N/Av	N/Av		

EBGELC Page 5 of 11

SAFETY DATA SHEET

Carbon dioxide	5000 ppm	30 000 ppm	5000 ppm (9000 mg/m³)	N/Av
d-Limonene	30 ppm (AIHA WEEL)	N/Av	N/Av	N/Av
Crystalline silica, quartz	0.025 mg/m³ (respirable)	N/Av	0.1 mg/m³ (respirable) (final rule limit)	N/Av

Exposure controls

Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient

ventilation wear suitable respiratory equipment.

Respiratory protection : If airbourne concentrations are above the permissible exposure limit or are not known, use

NIOSH-approved respirators. Refer to CSA Z94.3 or other appropriate standards. Advice

should be sought from respiratory protection specialists.

Skin protection: Wear protective gloves/clothing. The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Wear resistant clothing and boots. Depending on

conditions of use, an impervious apron should be worn.

Eye / face protection : Wear eye/face protection. Wear as appropriate: Tightly fitting safety goggles; Safety glasses

with side shields. A full face shield may also be necessary.

Other protective equipment : Ensure that eyewash stations and safety showers are close to the workstation location.

Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Wash

thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice. Contaminated work clothing

should not be allowed out of the workplace.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Grey liquid slurry, contained in pressurized aerosol can.

Odour : Petroleum odour.

 $\begin{array}{cccc} \textbf{Odour threshold} & : & \text{N/Av} \\ \textbf{pH} & : & \text{N/Av} \\ \end{array}$

Melting/Freezing point : Melting point: N/Av

Freezing point: N/Av

Initial boiling point and boiling range

: 227°C (440.6°F) (estimation)

Flash point : 87.8°C (190°F)
Flashpoint (Method) : Tag closed cup

Evaporation rate (BuAe = 1) : N/Av

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

: 0.7% (estimation)

Upper flammable limit (% by vol.)

: 5% (estimation)

Oxidizing properties : No oxidizing properties.

Explosive properties: Aerosols are sensitive to mechanical impact. Closed containers are contained under

pressure and may explode if exposed to excess heat for a prolonged period of time.

Vapour pressure : 0.59 hPa (estimated)

Vapour density : N/Av Relative density / Specific gravity

: Relative density: 920 kg/m³

Specific Gravity: 0.91

Solubility in water : Emulsifies
Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

ENGINE BRITE GEL

SDS Preparation Date (mm/dd/yyyy): 03/31/2023

SAFETY DATA SHEET

Auto-ignition temperature : N/Av **Decomposition temperature** : N/Av

Viscosity : 15 mm²/sec @ 40°C (104°F)

Volatiles (% by weight) : 2.09%
Volatile organic Compounds (VOC's)

: < 10%

Absolute pressure of container

: N/Av : None.

Flame projection length : None
Other physical/chemical comments

: Flashback Observed: NO Heat of combustion: 35.4 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization does not occur.

Conditions to avoid : Direct sources of heat. Do not use in areas without adequate ventilation. Avoid contact with

incompatible materials. Protect from sunlight and do not expose to temperatures exceeding

EBGELC Page 6 of 11

50 °C/122 °F.

Incompatible materials : Strong oxidizing agents; Strong acids; Strong alkalis; Halogenated compounds

Hazardous decomposition products

: Not available.

Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption

: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

• Mild respiratory irritant May cause coughing and breathing difficulties. Inhalation of high concentrations may cause dizziness, disorientation, incoordination, narcosis, nausea or narcotic effects. In extremely high concentrations, product may act as an asphyxiant and cause increased breathing and pulse rates, fatigue and unconsciousness.

Sign and symptoms ingestion

: May be fatal if swallowed and enters airways. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin : Causes skin irritation. Contact may cause redness, swelling and a painful sensation. May be

absorbed through the skin. If product is sprayed directly on skin, symptoms of frostbite may

be experienced including numbness, prickling and itching.

Sign and symptoms eyes : Causes serious eye irritation. Contact may cause redness, swelling and a painful sensation.

ENGINE BRITE GEL EBGELC

Page 7 of 11

SAFETY DATA SHEET

Potential Chronic Health Effects

 Prolonged or repeated skin exposure may cause redness, a burning sensation, drying and cracking of the skin (dermatitis). Prolonged overexposure may cause slight kidney effects, such as increased organ weight.

Mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

: This material is classified as hazardous under Canadian WHMIS regulations (Hazardous

Products Regulations) (WHMIS 2015). Classification:

Carcinogenicity - Category 1. May cause cancer. Symptoms may include persistent

coughing, shortness of breath, coughing up blood and wheezing.

Contains crystalline silica. Crystalline silica is classified as carcinogenic by IARC (Group 1),

the ACGIH (Category A2) and the NTP (Group 1 - Known human carcinogen).

Reproductive effects & Teratogenicity

: This product is not expected to cause reproductive or developmental effects.

Sensitization to material

: This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Skin sensitization - Category 1. May cause an allergic skin reaction. May cause severe skin sensitization with allergic contact dermatitis symptoms such as swelling, rash and eczema.

Contains: d-Limonene.

No data available to indicate product or components may be respiratory sensitizers.

Specific target organ effects

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous

Products Regulations) (WHMIS 2015). Classification:

Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or

dizziness.

According to the classification criteria of Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause specific target organ toxicity (STOT) through repeated exposures.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials Toxicological data

: None known or reported by the manufacturer.

: Not classified for acute toxicity based on available data. No data is available on the product itself. The calculated ATE values for this mixture are:

ATE oral = 95,238 - 103,286 mg/kg ATE dermal = 42,530 - 48,318 mg/kg ATE inholation (mists) = 230 - 261.5 mg/kg

ATE inhalation (mists) = 230 - 261.5 mg/L/4H

See below for individual ingredient acute toxicity data.

	LC₅₀ (4hr)	LD:	50
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)
Distillates (petroleum), hydrotreated light	> 5.2 mg/L (aerosol) (No mortality)	> 5000 mg/kg	> 2000 mg/kg (No mortality)
Solvent naphtha (petroleum), heavy aromatic	> 17.1 mg/L (mist)	> 6000 mg/kg	> 3160 mg/kg
Polyoxyethylene Sorbitol Hexaoleate	N/Av	16 000 mg/kg	N/Av
Carbon dioxide	200 000 ppm/2H (141 421 ppm/4H)	N/Ap(gas)	N/Ap(gas)
d-Limonene	N/Av	4400 mg/kg	> 5000 mg/kg
Crystalline silica, quartz	N/Av	N/Av	N/Av

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Toxic to aquatic life with long lasting effects. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. The product contains the following substances which are hazardous for the environment: Distillates (petroleum), hydrotreated light; Solvent naphtha (petroleum), heavy aromatic; d-Limonene.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	2.2.1	Toxicity to Fish			
	CAS No	LC50 / 96h	NOEC / 21 day	M Factor	
Distillates (petroleum), hydrotreated light	64742-47-8	20 mg/L (Rainbow trout) (Read-across)	N/Av	None.	
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	3.6 mg/L (Rainbow trout)	N/Av	None.	
Polyoxyethylene Sorbitol Hexaoleate	57171-56-9	N/Av	N/Av	None.	
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap	
d-Limonene	5989-27-5	0.72 mg/L (Fathead minnow)	N/Av	1	
Crystalline silica, quartz	14808-60-7	N/Av	N/Av	None.	

<u>Ingredients</u>	CAS No	Toxicity to Daphnia			
		EC50 / 48h	NOEC / 21 day	M Factor	
Distillates (petroleum), hydrotreated light	64742-47-8	40 - 89 mg/L (Daphnia magna) (Read-across)	0.48 mg/L (Read-across)	None.	
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	1.1 mg/L (Daphnia magna)	N/Av	None.	
Polyoxyethylene Sorbitol Hexaoleate	57171-56-9	N/Av	N/Av	None.	
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap	
d-Limonene	5989-27-5	0.36 mg/L (Daphnia magna)	N/Av	1	
Crystalline silica, quartz	14808-60-7	N/Av	N/Av	None.	

<u>Ingredients</u>	CAS No	Toxicity to Algae				
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor		
Distillates (petroleum), hydrotreated light	64742-47-8	6.2 mg/L/96hr (Green algae) (Read-across)	0.4 mg/L/96hr	None.		
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	7.2 mg/L/72hr (Green algae)	0.22 mg/L/72hr	None.		
Polyoxyethylene Sorbitol Hexaoleate	57171-56-9	N/Av	N/Av	None.		
Carbon dioxide	124-38-9	N/Ap	N/Ap	N/Ap		
d-Limonene	5989-27-5	N/Av	N/Av	None.		
Crystalline silica, quartz	14808-60-7	N/Av	N/Av	None.		

Persistence and degradability

: The product itself has not been tested.

The following ingredients are considered to be readily biodegradable: Distillates (petroleum),

hydrotreated light; d-Limonene.

Contains the following chemicals which are not readily biodegradable: Solvent naphtha (petroleum), heavy aromatic; Polyoxyethylene Sorbitol Hexaoleate; Crystalline silica, quartz.

Bioaccumulation potential

: The product itself has not been tested. See the following data for ingredient information.

Components	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	5.1 - 8.8	N/Av
Solvent naphtha (petroleum), heavy aromatic (CAS 64742-94-5	> 3, < 6.5	N/Av
d-Limonene (CAS 5989-27-5)	4.57	660

Mobility in soil

: The product itself has not been tested.

Other Adverse Environmental effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8. This material and its container must be disposed of in a safe way. Empty containers retain residue and can be dangerous. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal

: Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	none	2
TDG Additional information		as LIMITED QUANTITY when transported in containers no lar ss. Under the TDG, refer to Section 1.17 for additional exempti			

Special precautions for user

 Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards

This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:

Distillates (petroleum), hydrotreated light (Part 5: Other groups and mixtures)

Solvent naphtha (petroleum), heavy aromatic (Part 5: Other groups and mixtures)

d-Limonene (Part 5: Individual Substances)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	Present	Present	(9)-1700	KE-12550	Present	May be used as a single component chemical under an appropriate group standard.
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	265-198-5	Present	Present	(9)-2578	KE-31656	Present	May be used as a single component chemical under an appropriate group standard.
Polyoxyethylene Sorbitol Hexaoleate	57171-56-9	Not available.	Present	Present	(7)-110	KE-27610	Present	May be used as a component in a product covered by a group standard, but is not approved for use as a chemical in its own right.
Carbon dioxide	124-38-9	204-696-9	Present	Present	(1)-310; (1)-169	KE-04683	Present	HSR001018
d-Limonene	5989-27-5	227-813-5	Present	Present	(3)-2245; (3)-2226	KE-24397	Present	HSR002725
Crystalline silica, quartz	14808-60-7	238-878-4	Present	Present	(1)-548	KE-29983	Present	HSR003125

SECTION 16. OTHER INFORMATION

Legend : ACGIH: Ame

: ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances AIHA: American Industrial Hygiene Association

CAS: Chemical Abstract Services CSA: Canadian Standards Association EC50: Effective Concentration 50%

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

IBC: Intermediate Bulk Container

IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods

IOC: Inventory of Chemicals

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration
LD: Lethal Dose
N/Ap: Not Applicable

N/Ap: Not Applicable N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration NTP: National Toxicology Program

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RTECS: Registry of Toxic Effects of Chemical Substances

SDS: Safety Data Sheet

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TSCA: Toxic Substance Control Act

TWA: Time Weighted Average

WEEL: Workplace Environmental Exposure Level

WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2018.
 - 2. International Agency for Research on Cancer Monographs, searched 2019.
 - Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2019 (Chempendium, HSDB and RTECs).
 - 4. Material Safety Data Sheets from manufacturer.
 - 5. OECD The Global Portal to Information on Chemical Substances eChemPortal, 2019.

Preparation Date (mm/dd/yyyy)

: 03/31/2023

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for:

Blaster Holdings, LLC 8500 Sweet Valley Drive Valley View, Ohio 44125 USA T (216)901-5800 (US) (800)858-6605 (Canada)

Please direct all enquiries to Blaster Holdings, LLC

Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com



DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Blumenthal Brands Integrated, LLC and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc., Blumenthal Brands Integrated, LLC and B'laster Holdings, LLC expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and B'laster Holdings, LLC.