BBI

SAFETY DATA SHEET

1. Identification

Product identifier LT408 Liquid Wrench Pro Penetrant and Lubricant Spray

Other means of identification

SDS number LT408/6 Part No. LT408

Tariff code 3403.19.1000

Recommended use lubricant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Blumenthal Brands Integrated, LLC

Address 600 Radiator Road

Indian Trail, NC 28079

Telephone Customer Service/ (704) 821-7643

Technical

Website www.solvewithB.com
E-mail sds@solvewithB.com

Emergency phone number INFOTRAC (United States) (800) 535-5053

INFOTRAC (International) (352) 323-3500

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2

Health hazards Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable aerosol. May be fatal if swallowed and enters airways. May cause drowsiness or

dizziness. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist/vapor. Use only outdoors or in a well-ventilated area. Avoid release to the

environment.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled:

Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you

feel unwell. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Combustible.

Supplemental information

16.4, 16.4% of the mixture consists of component(s) of unknown acute oral toxicity.

21.26, 21.26% of the mixture consists of component(s) of unknown acute dermal toxicity. 16.52% of the mixture consists of component(s) of unknown acute inhalation toxicity. 21.26% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 21.26% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients

M	ixtı	ires
171	IALL	ai es

Chemical name	Common name and synonyms	CAS number	%
Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic		64742-52-5	40 - < 50
Distillates (petroleum), Hydrotreated Light	Hydrotreated light distillates (petroleum)	64742-47-8	20 - < 30
2,2,4-trimethyl-1,3-pentandiolmono sobutyrat (texanol)		25265-77-4	3 - < 5
Carbon Dioxide		124-38-9	1 - < 3
ВНТ		128-37-0	< 0.2
Calcium Carbonate		471-34-1	< 0.2
Oleoyl Sarcosine		110-25-8	< 0.2
Vanilla Mask Fragrance		Mixture	< 0.2
Other components below reportable	e levels		10 - < 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison Inhalation

center or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Most important Headache. Nausea, vomiting.

symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards

Flammable aerosol. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium Carbonate (CAS 471-34-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	PEL	400 mg/m3	
		100 ppm	
Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.

Components	Туре	Value	Form
		2000 mg/m3	
		500 ppm	
US. ACGIH Threshold Lim	it Values		
Components	Туре	Value	Form
BHT (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
BHT (CAS 128-37-0)	TWA	10 mg/m3	
Calcium Carbonate (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
ogical limit values	No biological exposure limits noted fo	r the ingredient(s).	
ropriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level.		
=	s, such as personal protective equipme		
Eye/face protection	Chemical respirator with organic vapo	r cartridge and full facepiece.	
Skin protection Hand protection	Wear appropriate chemical resistant <u>c</u>	lloves.	
Other			
Respiratory protection	Wear appropriate chemical resistant on Chemical respirator with organic vapor	<u> </u>	Chemical respirator with
respiratory protection	organic vapor cartridge and full facepi		
Thermal hazards	Wear appropriate thermal protective of	lothing when necessary	

When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

General hygiene

considerations

Physical state Liquid.
Form Aerosol.
Color Not available.
Odor Not available.

Odor threshold Not available.
pH Not available.

Melting point/freezing point -49 °F (-45 °C) estimated

Initial boiling point and boiling

range

585.37 °F (307.43 °C) estimated

Flash point > 200.0 °F (> 93.3 °C) Tag Closed Cup

Evaporation rateNot available.Flammability (solid, gas)Not applicable.Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 % estimated

(%)

Flammability limit - upper

5 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.20001 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 449.6 °F (232 °C) estimated

Decomposition temperature Not available.

Viscosity 58 cSt

Viscosity temperature 77 °F (25 °C)

Other information

Density 8.00523 lbs/gal estimated

Explosive properties Not explosive.

Flame extension 0 cm Flame projection 0 cm

Flammability class Combustible IIIB estimated

Heat of combustion 31.3 kJ/g estimated

Heat of combustion (NFPA

30B)

31.3 kJ/g

Oxidizing properties

Percent volatile

Specific gravity

VOC

Not oxidizing.

0.02 % estimated

0.95928 estimated

0 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions
Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: LT408 Liquid Wrench Pro Penetrant and Lubricant Spray LT408 Version #: 02 Revision date: 03-26-2020 Issue date: 05-07-2019

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components Species Test Results

2,2,4-trimethyl-1,3-pentandiolmonoisobutyrat (texanol) (CAS 25265-77-4)

<u>Acute</u>

Oral LD50

Rat 1600 - 3200 mg/kg

BHT (CAS 128-37-0)

<u>Acute</u>

Dermal

LD50 Rat > 2000 mg/kg, 4 wk (3 x/wk)

Oral

LD50 Rat > 6000 mg/kg

Calcium Carbonate (CAS 471-34-1)

Acute Oral

LD50 Rat 6450 mg/kg

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

Vapor

LC50 Rat > 4.5 mg/l, 4 Hours

> 0.1 mg/l, 8 Hours

Oral

LD50 Rat > 5000 mg/kg

Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 3.9 mg/l, 4 Hours

Oral

LD50 Rat > 2000 mg/kg

Oleoyl Sarcosine (CAS 110-25-8)

<u>Acute</u>

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

BHT (CAS 128-37-0) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Known To Be Human Carcinogen.

Heavy Naphthenic (CAS 64742-52-5)

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components Species Test Results

BHT (CAS 128-37-0)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 1.44 mg/l, 48 hours

Calcium Carbonate (CAS 471-34-1)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) > 56000 mg/l, 96 hours

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Persistence and degradability

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours

Fish LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.9 mg/l, 96 hours

(Chochiyhorido my

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

No data is available on the degradability of any ingredients in the mixture.

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity), MARINE POLLUTANT (Petroleum

Distillates), Limited Quantity

Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) 2.1

Not available. Packing group

Environmental hazards

Yes Marine pollutant

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions Packaging exceptions 306 Packaging non bulk None Packaging bulk None

IATA

UN1950 **UN** number

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity), Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not available.

Environmental hazards Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN1950 **UN number**

Aerosols, flammable, (each not exceeding 1 L capacity), MARINE POLLUTANT (Petroleum **UN proper shipping name**

Distillates), Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Not available. Packing group

Environmental hazards

Marine pollutant Yes

EmS Not available.


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Petroleum Distillates

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code



Material name: LT408 Liquid Wrench Pro Penetrant and Lubricant Spray LT408 Version #: 02 Revision date: 03-26-2020 Issue date: 05-07-2019

IATA



Marine pollutant



General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard

categories

Flammable (gases, aerosols, liquids, or solids)

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic (CAS 64742-52-5)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

 Issue date
 05-07-2019

 Revision date
 03-26-2020

Version # 02

United States & Puerto Rico

HMIS® ratings Health: 3

Flammability: 4 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 3 Instability: 0

NFPA ratings

2 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Physical & Chemical Properties: Multiple Properties

No