

1. Identification

Product identifier **Tite Seal Mower Deck Spray & Protectant**

Other means of identification

SDS number MDS11
Part No. MDS11
Tariff code 3403.19.1000

Recommended use Mower Deck Protectant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Blumenthal Brands Integrated, LLC
Address 600 Radiator Road
 Indian Trail, NC 28079
Telephone Customer Service/ (704) 821-7643
 Technical
Website www.solvewithB.com
E-mail sds@solvewithB.com
Emergency phone number INFOTRAC (United States) (800) 535-5053
 INFOTRAC (International) (352) 323-3500

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, dermal	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 1
	Carcinogenicity	Category 1A
	Reproductive toxicity	Category 1A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Aspiration hazard	Category 1
	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

13.42% of the mixture consists of component(s) of unknown acute oral toxicity. 21.64% of the mixture consists of component(s) of unknown acute dermal toxicity. 10.33% of the mixture consists of component(s) of unknown acute inhalation toxicity. 8.57% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 3.09% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Light Aromatic Hydrocarbon	(8052-41-3 and/or 64742-88-7 and /or 64742-48-9)	Trade Secret	50 - < 60
1,2,4-Trimethylbenzene		95-63-6	5 - < 10
Nonane		111-84-2	5 - < 10
Trimethylbenzene		25551-13-7	5 - < 10
Xylene		1330-20-7	5 - < 10
Carbon Dioxide		124-38-9	3 - < 5
Dimethicone		63148-62-9	3 - < 5
Cumene		98-82-8	1 - < 3
Ethylbenzene		100-41-4	1 - < 3
Hexane		110-54-3	1 - < 3
Toluene		108-88-3	1 - < 3
Benzene		71-43-2	< 1
Naphthalene		91-20-3	< 1
Polytetrafluoroethylene (PTFE)		111-77-3	< 1
Other components below reportable levels			5 - < 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
--------------------------------------	---

**Conditions for safe storage,
including any incompatibilities**

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m ³
		5000 ppm
Cumene (CAS 98-82-8)	PEL	245 mg/m ³
		50 ppm
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m ³
		100 ppm
Hexane (CAS 110-54-3)	PEL	1800 mg/m ³
		500 ppm
Naphthalene (CAS 91-20-3)	PEL	50 mg/m ³
		10 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m ³
		100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Benzene (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm
Benzene (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Cumene (CAS 98-82-8)	TWA	50 ppm
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Hexane (CAS 110-54-3)	TWA	50 ppm
Naphthalene (CAS 91-20-3)	TWA	10 ppm
Nonane (CAS 111-84-2)	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	20 ppm
Trimethylbenzene (CAS 25551-13-7)	TWA	25 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3
		25 ppm
Benzene (CAS 71-43-2)	STEL	1 ppm
	TWA	0.1 ppm
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3
		30000 ppm
	TWA	9000 mg/m3
Cumene (CAS 98-82-8)		5000 ppm
	TWA	245 mg/m3
		50 ppm
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
Hexane (CAS 110-54-3)		100 ppm
	TWA	180 mg/m3
		50 ppm
Naphthalene (CAS 91-20-3)	STEL	75 mg/m3
		15 ppm
	TWA	50 mg/m3
Nonane (CAS 111-84-2)		10 ppm
	TWA	1050 mg/m3
		200 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
Trimethylbenzene (CAS 25551-13-7)		100 ppm
	TWA	125 mg/m3
		25 ppm
Xylene (CAS 1330-20-7)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Benzene (CAS 71-43-2)	25 µg/g	S-Phenylmercapturic acid	Creatinine in urine	*

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Cumene (CAS 98-82-8)	Can be absorbed through the skin.
Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Liquid Milky.

Physical state	Liquid.
Form	Aerosol.
Color	Yellow
Odor	Mineral Spirits
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-55.54 °F (-48.63 °C) estimated
Initial boiling point and boiling range	314.6 °F (157 °C) estimated
Flash point	104.0 °F (40.0 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.29331 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	229 °F (109.44 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Aerosol spray ignition distance	75 - 15 cm
Density	6.69 lbs/gal
Explosive properties	Not explosive.
Flame extension	< 29 in
Flammability (flash back)	No
Flammability class	Combustible II estimated
Heat of combustion (NFPA 30B)	38 kJ/g estimated
Kinematic viscosity	< 5 cSt estimated
Kinematic viscosity temperature	104 °F (40 °C) estimated
Moisture	< 0.1
Oxidizing properties	Not oxidizing.
Percent volatile	14.7 % estimated
Refractive index	1.43
Specific gravity	0.802
VOC	85.28 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens. Nitrates. Peroxides.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Causes serious eye damage.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful in contact with skin.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Oral		
LD50	Rat	6 g/kg
Benzene (CAS 71-43-2)		
Acute		
Oral		
LD50	Rat	3306 mg/kg 690 - 1230 mg/kg
Cumene (CAS 98-82-8)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Mouse	10 mg/l, 7 Hours
Oral		
LD50	Rat	2260 mg/kg
Ethylbenzene (CAS 100-41-4)		
Acute		
Oral		
LD50	Rat	3500 mg/kg
Hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours

Components	Species	Test Results
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 31.86 mg/l, 4 Hours
Oral		
LD50	Rat	28710 mg/kg
Light Aromatic Hydrocarbon		
Acute		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	> 2000 mg/kg
Oral		
<i>Liquid</i>		
LD50	Rat	> 5000 mg/kg
Naphthalene (CAS 91-20-3)		
Acute		
Dermal		
LD50	Rabbit	> 2 g/kg
Oral		
LD50	Rat	490 mg/kg
Polytetrafluoroethylene (PTFE) (CAS 111-77-3)		
Acute		
Dermal		
LD50	Rabbit	6540 mg/kg
Oral		
LD50	Rat	5500 mg/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	12.5 - 28.8 mg/l, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
Trimethylbenzene (CAS 25551-13-7)		
Acute		
Oral		
LD50	Rat	8970 mg/kg
Xylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	12130 mg/kg, 24 Hours
Inhalation		
LC50	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Rat	3523 - 8600 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	

Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Benzene (CAS 71-43-2)	1 Carcinogenic to humans.
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Naphthalene (CAS 91-20-3)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Benzene (CAS 71-43-2)	Cancer
-----------------------	--------

US. National Toxicology Program (NTP) Report on Carcinogens

Benzene (CAS 71-43-2)	Known To Be Human Carcinogen.
Cumene (CAS 98-82-8)	Reasonably Anticipated to be a Human Carcinogen.
Naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.19 - 8.28 mg/l, 96 hours
Benzene (CAS 71-43-2)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 7.2 - 11.7 mg/l, 96 hours
Cumene (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (<i>Artemia sp.</i>) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 2.7 mg/l, 96 hours
Dimethicone (CAS 63148-62-9)		
Aquatic		
Fish	LC50	Channel catfish (<i>Ictalurus punctatus</i>) 2.36 - 4.15 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.5 - 11 mg/l, 96 hours
Hexane (CAS 110-54-3)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.101 - 2.981 mg/l, 96 hours

Components	Species	Test Results
Naphthalene (CAS 91-20-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha) 1.11 - 1.68 mg/l, 96 hours
Polytetrafluoroethylene (PTFE) (CAS 111-77-3)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) 7500 mg/l, 96 hours
Toluene (CAS 108-88-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Benzene	2.13
Cumene	3.66
Ethylbenzene	3.15
Hexane	3.9
Naphthalene	3.3
Nonane	5.46
Toluene	2.73
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F D018: Waste Benzene The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity), Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1

Packing group	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA


UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, MARINE POLLUTANT (Mineral Spirits NE), Limited Quantity
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Mineral Spirits NE	


Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT; IMDG



IATA





15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Nonane (CAS 111-84-2) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Benzene (CAS 71-43-2)	Listed.
Cumene (CAS 98-82-8)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Hexane (CAS 110-54-3)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Nonane (CAS 111-84-2)	Listed.
Polytetrafluoroethylene (PTFE) (CAS 111-77-3)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Benzene (CAS 71-43-2)	Cancer Central nervous system Blood Aspiration Skin Eye respiratory tract irritation Flammability
-----------------------	--

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Germ cell mutagenicity Carcinogenicity Reproductive toxicity Specific target organ toxicity (single or repeated exposure) Aspiration hazard
-------------------------------------	--

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	5 - < 10
Benzene	71-43-2	< 1
Cumene	98-82-8	1 - < 3
Ethylbenzene	100-41-4	1 - < 3
Hexane	110-54-3	1 - < 3
Naphthalene	91-20-3	< 1
Polytetrafluoroethylene (PTFE)	111-77-3	< 1
Toluene	108-88-3	1 - < 3

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Xylene	1330-20-7	5 - < 10

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Benzene (CAS 71-43-2)
 Cumene (CAS 98-82-8)
 Ethylbenzene (CAS 100-41-4)
 Hexane (CAS 110-54-3)
 Naphthalene (CAS 91-20-3)
 Polytetrafluoroethylene (PTFE) (CAS 111-77-3)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations**California Proposition 65**

WARNING: This product can expose you to chemicals including naphthalene, which are known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987
 Cumene (CAS 98-82-8) Listed: April 6, 2010
 Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004
 Naphthalene (CAS 91-20-3) Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997
 Toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)
 Benzene (CAS 71-43-2)
 Cumene (CAS 98-82-8)
 Ethylbenzene (CAS 100-41-4)
 Hexane (CAS 110-54-3)
 Naphthalene (CAS 91-20-3)
 Polytetrafluoroethylene (PTFE) (CAS 111-77-3)
 Toluene (CAS 108-88-3)
 Trimethylbenzene (CAS 25551-13-7)
 Xylene (CAS 1330-20-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-23-2015
Revision date	03-30-2020
Version #	03
HMIS® ratings	Health: 3* Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 2 Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Physical & Chemical Properties: Multiple Properties