



GR011 Plastic Tube, 14oz.  
078698217826

## MULTI-PURPOSE GREASE

GR011

**LIQUID WRENCH® MULTI-PURPOSE GREASE** for general-purpose lubrication around the shop and farm. Operating temperature range of -10°F to 200°F. Recommended for applications that do not require anti-wear or extreme pressure agents. This is a multi-purpose lubricating grease formulated in high quality base oil. This Multi-Purpose Grease is excellent for general applications that do not require additional anti-wear or extreme pressure agents.

### APPLICATIONS:

- General Multi-Purpose Grease
- For Farm, Home and Shop
- For Light-To-Medium Duty Lubrication
- Lubricates Rolling Parts, Linkages And Levers

### TYPICAL PROPERTIES:

NLGI Grade: 1 ½	Soap Contents % (wt): 6 – 9
Thickener: Lithium/Mixed Base	Worked Penetration @ 77°F, ASTM D 217: 290 – 320
Texture: Smooth, Buttery	Dropping Point, (°F), Min, ASTM D 2265: 350
Color: Gray/Black	Water Washout, 175°F, Max: 15%
Base Oil Characteristics	
Pour Point °F (°C), ASTM D 97: 0 (-18)	
Viscosity @ 100°C, cSt: 10.0 – 12.5	
Viscosity @ 40°C, cSt: 113 – 165	
Viscosity @ 210°F, SUS: 60 – 70	
Viscosity @100°F, SUS: 600 – 884	
Viscosity Index, Min: 50	

**DIRECTIONS:** Do not mix greases of different types. Thoroughly remove old grease before applying.

**DANGER:** Eye and skin irritant. Avoid contact with eyes and prolonged or repeated contact with skin. Wash hands after using product. May be harmful if swallowed.

**FIRST AID:** EYE CONTACT: Flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician or Hospital Emergency Room immediately.

**KEEP AWAY FROM CHILDREN AND ANIMALS**

NOTICE: While this information is presented in good faith and believed to be accurate, Blumenthal Brands Integrated, LLC does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Blumenthal Brands Integrated, LLC disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.