

HS3K

Pail, 1.75 gal. 078698819044

## HYDRO SEAL® II PARTS CLEANER HEAVY DUTY

HS3K

**GUNK**° **Hydro Seal**° **II Heavy Duty Parts Cleaner** is for use in solvent cleaning tanks or related equipment. Powerful parts cleaning compound with no chlorinated solvents. Includes dip basket. Safe on all metals, including carbon steel, stainless steel, aluminum, brass, copper, nickel and chrome.

## **APPLICATIONS:**

Use on engine blocks, crankshafts, automatic transmissions and other engine parts.

**DIRECTIONS:** NOT FOR USE ON PLASTICS OR RUBBER. USE TO IMMERSION CLEAN PISTONS, RODS, PUSH RODS, CYLINDER HEADS, TRANSMISSION PARTS, OIL, PAN, DIFFERENTIAL PARTS, BELL HOUSINGS, ETC. To aid cleaning action and lengthen active life of HYDRO SEAL® II, wipe off heavy residues before soaking. DO NOT HEAT OR AGITATE WITH COMPRESSED AIR - THIS PRODUCT SHOULD BE USED DAT ROOM TEMPERATURE. Cold temperatures lessen the cleaning effectiveness and prolong required soaking times. As with all solvents, safety goggles and gloves should be worn when handling. Must read SDS (Safety Data Sheet) before using this product. SDS's are available at gunk.com.

- 1. Place parts in cleaning basket and soak in HYDRO SEAL® II until clean. Soak parts below surface. (Periodic lifting, shaking and rotating of cleaning basket with parts will speed up cleaning action.) Keep container covered to prevent evaporation.
- 2. Brush heavy deposits and continue soaking. Check the cleaning progress by lifting the basket and examining the part.
- 3. When parts are clean, rinse with water. Dry parts with towels. To protect clean parts from rusting, spray with a light film of LIQUID WRENCH® Rust Inhibitor, Part No. LC9/6

**STORAGE, HANDLING & DISPOSAL:** Store in a cool, dry well-ventilated area away from oxidizers and ignition sources. Do not expose contents or put container in contact with heat, sparks or open flame. Wear safety goggles or full face shield, rubber gloves and protective apron. SAFEGUARD OUR ENVIRONMENT. The residue resulting from the removal of petroleum oils and greases may be considered a hazardous waste depending upon where and how generated. The use of this product to clean engines and bilges in watercraft produces a hazardous waste that cannot be discharged into any waterway. Disposal of contaminated rinse water into watercourses, sewers, or on the ground may also be prohibited by law. Such disposal is prohibited in California. Proper disposal includes collecting and evaporating rinse water and/or recycling and disposal of residues and the empty container in accordance with all local, state, and federal laws and regulations.

**FIRST AID:** Eye irritant. EYES: for eye contact, flush with water for 15 minutes while lifting eyelids. If irritation develops, get prompt medical attention. SKIN: in case of skin contact, wash with soap and water. If irritation develops, get prompt medical attention. INHALATION: If inhaled, move to fresh air. If breathing becomes difficult get prompt medical attention. INGESTION: HARMFUL OR FATAL IF SWALLOWED. Do not induce vomiting. Call Poison Control Center, Physician, or Hospital Emergency Room immediately.



CALIFORNIA PROP 65 WARNING: This product can expose you to chemicals including naphthalene which are known to the State of California to cause cancer, and 1-methyl-2-pyrrolidone, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## **KEEP AWAY FROM CHILDREN AND ANIMALS**

NOTICE: While this information is presented in good faith and believed to be accurate, Blumenthal Brands Integrated, LLC does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Blumenthal Brands Integrated, LLC disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

