

PRODUCT INFORMATION



HEAVY DUTY SPRAY LUBRICANT WITH PTFE

CODE: L508

PAGE: 1 OF 1

DATE: July 2012

FUNCTION AND APPLICATION: A more efficient, multi-purpose lubricant for use in home and industry.

OUTSTANDING PROPERTIES: Reduces friction, wear, penetrates, lubricates, cleans and protects, prevents rust and corrosion. The very small particles act as "ball bearings" to reduce friction significantly. Cleans and forms barrier which resists dust, dirt, sand, salt, ice, and other abrasive particles. Penetrates and dissolves rust and corrosion while preventing further corrosion. Can be used in thousands of applications. Some of the areas where this product can be used: Locks, Fishing Reels, Auto Parts, Hinges, Typewriters, Boat Parts, Guns, Sewing Machines, Cables, Toys, Sliding Doors, Chains, Clocks, Lawn Mowers, Linkages, Zippers, Air Conditioners, Gears, Hand Tools, Fine Instruments, Valves, Power Tools, Conveyor Parts, Fittings, Casters, Machine Tools, and more.

USE DIRECTIONS: Shake well before using. For lubrication or penetration, apply directly to part or equipment. Allow time for penetration (if parts are heavily corroded, scrape or wire brush, friction parts before applying. Penetration time will be longer depending on degree of corrosion.) Apply sufficient force to gradually loosen surfaces and make parts operable. As part operates, wipe away accumulated residue.

PRECAUTIONS: Contains (CAS#) Naphthenic Petroleum Oil Mixture (64742-52-5) and a hydrocarbon propellant. Harmful or fatal if swallowed. Eye and skin irritant. **FIRST AID:** If swallowed, do not induce vomiting. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. If eyes contacted, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. For inhalation, move to fresh air immediately. If breathing becomes difficult, get prompt medical attention.

STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 120 F. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Wearing contact lenses while working with this product is inadvisable. **KEEP AWAY FROM CHILDREN AND ANIMALS.**

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: Aerosol can, 6 oz net wt.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.