



M3332

Plastic Bottle, 32 oz.  
078698133331

# HYDRAULIC JACK OIL

M3332

**Liquid Wrench® Hydraulic Jack Oil** is made for use in all hydraulic jacks, snow plows and refillable shock absorbers. Intermixes completely with all other standard hydraulic jack fluids. This is an SAE 10 weight oil, ISO rating of 22, and 32 cSt at 40°C.

## BENEFITS:

- Formulated with extreme pressure anti-wear additives
- Oxidation & rust inhibitors
- Anti-foam agents
- Mixes with all standard hydraulic jack fluids
- Use in hydraulic jacks, snow plows & refillable shock absorbers that specify ISO 22 or SAE 10W fluid

**DIRECTIONS:** To keep foreign matter from entering fluid chamber, wipe fill plug and area around it before removing plug from chamber. Follow manufacturer's recommendations for proper fill level. Keep fill at maximum level at all times. To keep hydraulic equipment in good condition, periodically drain system and refill with fresh liquid. **CAUTION:** Do not use in hydraulic brake systems or automatic transmissions.

**STORAGE, HANDLING & DISPOSAL:** Dispose of product, residue and the empty container in accordance with all local, state and federal laws and regulations.

**DANGER:** Do not take internally. Harmful if swallowed. Eye & skin irritant. Get Material Safety Data Sheet via [liquidwrench.com](http://liquidwrench.com).

**FIRST AID: EYES:** Flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. **SKIN:** Wash with soap and water. If irritation persists, get prompt medical attention. **INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Call Poison Control Center, physician or hospital emergency room immediately.



**CALIFORNIA PROP 65 WARNING:** This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**KEEP AWAY FROM CHILDREN AND ANIMALS**

NOTICE: While this information is presented in good faith and believed to be accurate, Blumenthal Brands Integrated, LLC does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Blumenthal Brands Integrated, LLC disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.