

PRODUCT INFORMATION



NON CHLORINATED BRAKE CLEANER (AEROSOL)

CODE: M714EE

PAGE: 1 of 1

DATE: February 2010

FUNCTION AND APPLICATION: Will help remove surface contaminants such as brake fluid, oil, and grease from brake linings, drums, other brake parts and CV joint assemblies. Degreases quickly and can be used without disassembling the brake unit. Brake pads or linings that are impregnated with oil or grease should be replaced, not cleaned.

OUTSTANDING PROPERTIES: Leaves no residue and dries quickly. Helps retard the release of asbestos dust and other airborne particulate matter when following directions. Use SOLDER SEAL® GUNK® BRAKE CLEANER on: conventional brake units, linings and shoes, drums, cylinders, springs, disc brake units C.V. joints, caliper units, brake pads, discs, and related parts. Contains no chlorinated solvents.

USE DIRECTIONS: First, turn engine off then lightly wet down surfaces to be cleaned by spraying in short bursts from a distance of 18 to 24 inches. **Do not spray on hot metal surfaces like exhaust pipes.** After the surfaces have been wetted, continue spraying at a distance of 12 to 18 inches to flush contaminants from surfaces. Spray brake parts thoroughly, then allow to air dry or wipe with soft clean cloth. If deposits are heavy, repeat application.

DANGER: Contains (CAS#) heptane (142-82-5) and carbon dioxide (124-38-9). Harmful or fatal if swallowed. Extremely flammable. Eye and skin irritant. Contents under pressure. Use only in well-ventilated area away from heat, sparks, and flame. Pilot lights of furnaces, hot water tanks or even static electricity can ignite vapors explosively. Do not use in confined spaces, enclosed garages, basements or low lying areas where vapors can collect. Do not place can on hot surfaces or in direct sunlight which could cause can to burst violently. Keep can away from contact with electrical current or connections such as battery terminals because burn through may occur. Explosion or flash fire from liquid or vapors may cause

Professional users must read the Material Safety Data Sheet (MSDS) before using this product. MSDS's are available to anyone upon request. 1-704-821-7643 or at www.gunk.com.

FIRST AID: For EYE contact: Flush thoroughly with water for 15 minutes lifting upper and lower eyelids occasionally and get prompt medical attention. For SKIN contact: Wash thoroughly with soap and water. If irritation develops, get prompt medical attention. IF SWALLOWED DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. Never give anything by mouth to an unconscious person. If INHALED, remove to fresh air. If breathing becomes difficult, get prompt medical attention.

STORAGE AND HANDLING: Store in a cool, dry, well ventilated area at temperatures below 120°F. Do not puncture, crush or incinerate (burn) can. KEEP AWAY FROM CHILDREN AND ANIMALS.

DISPOSAL: Disposal of product runoff in water courses, sewers, or on the ground is prohibited. Proper disposal includes collecting and recycling. Always use and dispose of product, container, and residue in accordance with all local, state and federal laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: This product is available in 14-oz (396g) aerosol container.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.