



M720 Aerosol Metal, 19 oz.
0786981300712

BRAKE PARTS CLEANER – CHLORINATED

Quickly removes brake fluid, dust build up and oil from brake parts and C.V. joint assemblies. Can be used without disassembling the brake unit. Dries completely and leaves no residue. Brake pads or linings that have been damaged (impregnated) with oil or grease should be replaced, not cleaned. To help retard the release of asbestos dust and other airborne particulate matter, follow the DIRECTIONS for use carefully. Professional Users must read the SDS before using this product. Call 704-821-7643 or go to www.gunk.com for SDS.

BENEFITS: Cleans better • Non-flammable • Quickly dissolves and flushes brake dust, brake fluid, grease and oil contaminants • Dries quickly

INSTANTLY dissolves brake fluid, grease & oil

- Non-Flammable
- Quick drying
- No residue
- Powerful solvent
- Extremely fast cleaning
- Powerful spray pattern

DIRECTIONS: 1. Turn off engine. 2. Protect rubber or plastic brake parts, seals and painted surfaces from spray. 3. Spray short bursts from a distance of 18-24 inches to wet parts. 4. Continue spraying at a distance of 12-18 inches to flush contaminants from surface. 5. Spray brake parts thoroughly and allow to air dry or wipe with a soft clean cloth. If deposits are heavy repeat application. **DO NOT SPRAY ON HOT METAL SURFACES LIKE EXHAUST PIPES. IMPORTANT: THIS PRODUCT WILL ATTACK PAINTED SURFACES AND PLASTIC - FLUSH WITH WATER IMMEDIATELY.**

STORAGE, HANDLING & DISPOSAL: **EXPLOSION HAZARD:** Contents under pressure. Do not place can on hot surfaces and do not expose to heat or direct which could cause can to burst violently and cause serious injury. Store in a dry, well-ventilated area below 120°F (49°C). Do not puncture, crush, or incinerate (burn) can. **BREATHING & CONTACT HAZARDS:** Do not breathe asbestos, dust particles, or product vapors. Use NIOSH-approved respirator. Use only in a well-ventilated area with a constant flow of fresh air, and open doors and windows to prevent vapor buildup. Combustion or high heat should be avoided as toxic decomposition may occur. **INHALING CONCENTRATED VAPORS, INTENTIONALLY OR OTHERWISE, CAN CAUSE BRAIN AND PERMANENT ORGAN DAMAGE OR CAN BE FATAL.** Avoid contact with eyes, skin, or clothing. Repeated contact may dry and defat the skin. Remove contact lenses before use. Wear chemical-resistant goggles and solvent-proof gloves and apron. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Dispose of product residue, rinse and empty container in accordance with all local, state and federal laws and regulations. Disposal of product runoff in water courses, sewers or on the ground is prohibited. Proper disposal includes collecting and recycling. Empty aerosol cans are recyclable: consult your local recycling authority. Emptied containers contain product residue, so follow all warnings, even after container is emptied.

FIRST AID: **EYE CONTACT:** Flush thoroughly with water for 15 minutes while occasionally lifting eyelids and get prompt medical attention. **SKIN CONTACT:** Wash thoroughly with soap and water. If irritation develops, get prompt medical attention. **INHALATION:** Move to fresh air. If breathing becomes difficult, get prompt medical attention. **INGESTION:** **DO NOT INDUCE VOMITING.** Call Poison Control Center, Physician, or Hospital Emergency Room immediately.

NOT FOR SALE IN CALIFORNIA OR NEW JERSEY

KEEP AWAY FROM CHILDREN AND ANIMALS

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.