



Aerosol Metal, 11.25 oz.
078698108582

Aerosol Metal, 2 oz.
078698117713

BRAKE PARTS PROTECTOR SQUEAL MEDIC

M725/6, M72502/12

GUNK® Squeal Medic, when applied to rotors or drums, stops brake noise before it starts. Squeal Medic delivers excellent noise suppression and break-in properties of the linings. When applied to the rotors and drums, Squeal Medic fills voids to help eliminate brake squeals cause by harmonic vibration resulting from uneven surfaces. Squeal Medic does not affect braking performance. Helps prevent oxidation of rotors and drums. Will not affect or damage the ABS sensors or rubber components of the braking system. Squeal Medic is effective on all vehicle brake systems, requires no drying time, and can be used as an anti-seize lubricant on lug nuts. Professional users must read the Material Safety Data Sheet before using this product. MSDS's are available at gunk.com.

APPLICATIONS:

- Prevents Squeals Before They Start
- For All Disc, Drum, & ABS Brakes
- For Use on Every Brake Job

DIRECTIONS: 1. Shake can well before using 2. Use on a clean system 3. Before assembling the unit, spray a light coat (2 seconds) directly onto the rotor or drum surface. Use sparingly. Then assemble the unit. 4. After assembling the unit, drive the vehicle applying the brakes 5 to 8 times while driving at low speed.

STORAGE, HANDLING & DISPOSAL: FIRE AND EXPLOSION HAZARD: EXTREMELY FLAMMABLE. Use only in a well-ventilated area away from heat, sparks, and flame. BREATHING & CONTACT HAZARDS: Ensure a constant flow of fresh air, especially in confined spaces such as enclosed garages or other low-lying areas where vapors can collect. EXPLOSION OR FLASH FIRE FROM VAPORS MAY CAUSE SERIOUS INJURY. Do not puncture, crush or incinerate (burn) can. Do not expose to heat, direct sunlight, or store at temperature above 120°F. INHALING CONCENTRATED VAPORS, INTENTIONALLY OR OTHERWISE CAN BE HARMFUL OR FATAL. Dispose of product residue, rinsate, and empty container in accordance with all local, state, and federal laws and regulations. Empty aerosol cans are recyclable: consult your local recycling authority. Emptied containers contain product residue, so follow all warnings, even after container is emptied.

DANGER: Extremely Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under Pressure.

FIRST AID: EYE CONTACT: Flush thoroughly with water for 15 minutes while lifting eyelids occasionally and get prompt medical attention. SKIN CONTACT: Wash with soap and water. If irritation persists, get prompt medical attention. INHALATION: Move to fresh air. If breathing becomes difficult, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.