

PRODUCT INFORMATION



PARTS WASHER SOLVENT

CODE: SCS-5

PAGE: 1 of 1

DATE: May 2008

FUNCTION AND APPLICATION: PARTS WASHER SOLVENT is a fast-acting, ready to use solvent blend designed for recirculating parts washer equipment.

USE DIRECTIONS: 1) Fill tank to level recommended by equipment manufacturer. 2) Surfaces to be cleaned should be moisture free (Moisture on surfaces to be cleaned may slow cleaning action).

3) Follow equipment manufacturer's recommendations on the use on this product. 4) After parts have been cleaned, allow parts to air dry for at least 15 minutes.

NOTE: This product cannot be used as an engine degreaser in California due to the VOC content which does not meet standards.

PRECAUTIONS: Contains Aliphatic Petroleum Distillate (CAS# 8052-41-3), Petroleum Distillate (CAS# 68476-34-6), Aliphatic Petroleum Oil (CAS# 64741-44-2), 2-Butoxy-1-Ethanol (CAS# 111-76-2), Sodium Petroleum Sulfonate (CAS# 68608-26-4), and Ethoxylated Nonyl-Phenol (CAS# 9016-45-9) Caution: Combustible. Eye and skin irritant. Exposure can cause severe irritation leading to redness and burning like sensation. Skin irritant. Repeated exposure of high concentration can cause irritation leading to defatting of tissue and dermatitis. Vapor harmful. Exposure to high concentration of mist and vapors can cause dizziness, narcosis, and headache. Repeated exposure may lead to kidney and liver damages. Harmful or fatal if swallowed. **FIRST AID:** If eye contacted, flush with water while lifting eyelids thoroughly for 15 minutes and get prompt medical attention. For skin contact, wash with soap and water thoroughly. Remove contaminated clothing. If adverse effects persist get prompt medical attention. For inhalation remove to fresh air. If breathing become difficult get prompt medical attention. If swallowed! DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately.

STORAGE AND HANDLING: Store in a cool, dry, well ventilated area away from oxidizers and ignition sources. Do not expose contents or put containers in contact with heat, sparks or open flame. Wear safety goggles or full face shield, rubber gloves and protective apron. Wearing contact lenses while working with this product is inadvisable. Keep away from children.

DISPOSAL: Do not reuse container for any purpose. Container must be disposed of according to all local, state and federal regulations. Empty container should be disposed of according to procedures approved by local, state and federal authorities. Consult the MSDS for further information. When disposing of unused contents, send to licensed reclaimers, or to authorized incinerators. Any disposal practice must comply with all local, state and federal regulations. Do not dump into sewers, on the ground, or into any body of water. All cautions apply to empty containers after product use.

CONTAINER DESCRIPTION: This product is available in 5-gallon containers.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.