



Aerosol Metal, 16 oz.
078698201610

AUTO BODY UNDERCOATING

T1616

Use TITSEAL™ AUTO BODY UNDERCOATING to protect your car body from rust and corrosion. Effective after repairs and on replacement parts. It seals out moisture and dust; deadens sound.

APPLICATIONS:

- Paintable
- Seals Against Rust & Corrosion
- Muffles Outside Noise
- Dampens Sound & Vibration

DIRECTIONS: For best results, contents should be sprayed above 50°F. Before using, shake well until agitator ball moves freely in can. Surface to be sprayed should be clean and dry. Hold can 12" to 16" from surface to be sprayed. Two or more thin coats will produce a better finished job. Completely dry between coats and before painting. Do not spray on catalytic converter or exhaust system. Clean nozzle after use by turning can upside down and pressing nozzle for about 3 seconds. If overspray occurs, use Gunk® Tar & Bug Remover for fast, easy removal.

STORAGE, HANDLING & DISPOSAL: Contents under pressure. Do not expose to heat, sparks, or flames. Do not store container above 120°F. Do not puncture or incinerate container. Dispose of in accordance with all applicable state and federal government laws and regulations.

DANGER: Extremely flammable. Harmful or fatal if swallowed. Eye and skin irritant. Use with adequate ventilation. **DO NOT TAKE INTERNALLY.**

FIRST AID: EYE CONTACT: Flush thoroughly with water for 15 minutes, while lifting eyelids and get prompt medical attention. SKIN CONTACT: Wash with soap and water. If irritation persists, get prompt medical attention. INHALATION: Move to fresh air. If breathing becomes difficult, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, physician, or hospital emergency room immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.